

Eaton Evolution

650/850/1150/1550/2000 VA



Line interactive

High density protection for network devices

Maximum availability

- **Powershare:** the Eaton Evolution output sockets are individually controlled to provide load-shedding to maximise the backup time and provide remote reboot and sequential start-up as standard
- **Continuous power supply:** Hot swappable batteries. The optional HotSwap MBP (Maintenance By-Pass) module allows the UPS to be replaced without interrupting the power supply
- **Pure sinewave output:** when operating in batterie mode the Eaton Evolution still provides high quality output signal for sensitive connected equipment

Minimum total cost of ownership

- **Line-interactive HF technology:** the best price/performance ratio
- **No additional cost:** rack 1U and RT models are provided with the rail kits
- **Remote supervision:** a wide range of options using the Eaton Software suite, including point-to-point power management, SNMP, relay outputs, etc...

Total flexibility

Evolution has unmatched flexibility.

- **Format:** Evolution is available in tower format, rack 1U format, RT2U convertible rack/tower (2kVA model)
- **Communication:** the Evolution includes both serial and USB ports, plus remote On/Off connector and an extra slot for optional communication cards. The UPS comes with a complete Eaton software suite.



1U tower model

Advanced protection for:

- Rack servers
- Tower servers
- Network devices
- Storage systems



Powering Business Worldwide

Eaton Evolution UPS

650/850/1150/1550/2000 VA

- 1 Full user interface:
 - ON/OFF button for UPS and outlets
 - Load protected/ not protected LED
 - Utilised power level/Battery charge level
 - Status of switchable outlets
- 2 Panel for batteries replacement (Hot swappable)



- 3 1 x USB port + 1 x serial port + remote ON/OFF
- 4 4 x IEC 10A sockets, including 2 programmable sockets
- 5 Communication card slot

Eaton Evolution 1550 Tower

Technical Specifications	650	850	1150	1550	2000
Rating (VA/W)	650 VA / 420 W	850 VA / 600 W	1150 VA / 770 W	1550 VA / 1100 W	2000 VA / 1600 W
Format	Tower or 1U Rack	Tower or 1U Rack	Tower or 1U Rack	Tower or 1U Rack	RT2U (tower / rack 2U)
Electrical characteristics					
Technology	Line-Interactive High Frequency (Booster + Fader)				
Input voltage and frequency ranges without using batteries	160V-294V (adjustable to 150V-294V) 47 to 70 Hz (50 Hz system), 56.5 to 70 Hz (60 Hz system), up to 40 Hz in low-sensitivity mode (programmable using Personal Solution-Pac software).				
Output voltage and frequency	230 V (+6/-10 %) (Adjustable to 200 V (10 % derating of output power) / 208 V / 220 V / 230 V / 240 V), 50/60 Hz +/- 0.1 %				
Connections					
Input	1 x IEC C14 (10A) socket				
Outputs	4 x IEC C13 (10A)	4 x IEC C13 (10A)	4 x IEC C13 (10A)	4 x IEC C13 (10A)	8 x IEC C13 (10 A)
Remotely controlled sockets	2 groups of 1 x IEC C13 (10A)	2 groups of 1 x IEC C13 (10A)	2 groups of 1 x IEC C13 (10A)	2 groups of 1 x IEC C13 (10A)	2 groups of 2 x IEC C13 (10A)
Additional outputs with HS MBP	4 x 3 Pin Aust or 6x IEC 10A sockets or terminal blocks (HW version)				
Additional outputs with FlexPDU	4 x 3 Pin Aust or 12 x IEC 10 A sockets				
Batteries					
Typical backup times for 50 and 70% load	9/6 min	16/7 min	14/7 min	14/7 min	14/7 min
Battery management	Automatic weekly test (period adjustable), automatic recognition of external battery units => continuous maximisation of backup time + deep discharge protection				
Interfaces					
Communication ports	1 x USB port + 1 x RS232 serial port and relay contacts (USB and RS232 ports cannot be used simultaneously) + 1 mini terminal block for remote ON/OFF and Remote Power Off				
Communications card slots	1 slot for NMC Minislot card or NMC ModBus/JBus or MC Contacts/Serial				
Operating conditions, standards and approvals					
Operating temperature	0 to 35°C	0 to 35°C	0 to 35°C	0 to 40°C	0 to 40°C
Noise level	< 40dba	< 40dba	< 40dba	< 40dba	< 45 dBA
Performance - Safety - EMC	IEC/EN 62040-1-1 (Safety), IEC/EN 62040-2 EN 50091-2 class B (EMC), IEC/EN 62040-3 (Performance), IEC/EN 61000-4-2, 61000-4-3, 61000-4-4; 61000-4-5, 61000-4-6, 61000-4-8 (EMI)				
Approvals	CE, CB report, TÜV				
Dimensions W x D x H / Weight					
Dimensions of the Tower	147 x 418 x 234 mm	147 x 418 x 234 mm	147 x 418 x 234 mm	147 x 492 x 234 mm	440 x 509 x 86.2 (2U) mm
Dimensions of the Rack	438 x 366 x 43.2 (1U)	438 x 512 x 43.2 (1U)	438 x 512 x 43.2 (1U)	438 x 556 x 43.2 (1U)	440 x 509 x 86.2 (2U)
Weight of the Tower/Rack	8.4/10.1 kg	10.85/16.1 kg	12.5/16.6 kg	16.53/20 kg	25.7 kg
Customer Service & Support					
2 years warranty	Standard product exchange, including the battery				
Warranty+	Optional 3-years warranty (depending on the country please visit www.eaton.com/powerquality)				

Part Numbers	650	850	1150	1550	2000 RT2U
Tower	M68450	M68452	M68454	M68457	/
Rack1U	M68451	M68453	M68455	M68458	/
Convertible Tower/Rack	/	/	/	/	M68460



Eaton Industries Pty. Ltd.
 Electrical Group
 Head Office:
 10 Kent Road Mascot,
 NSW 2020 Australia
 1300 UPS UPS (1300 877 877)
www.eaton.com/powerquality

LanSafe, Eaton, ePDU, Flex, PowerChain Management, PowerTrust, Powerware, PowerPass, X-Slot, and PowerVision are trade names, trademarks, and/or service marks of Eaton Corporation. All other trademarks are the property of their respective owners.

© 2008 Eaton Corporation
 All Rights Reserved
 Printed in AUS EVLFXA-AUS
 November 2008

